

T11 4,000 LITRE





Offshore Portable Tank



4,000 LITRE



A Marmon/Berkshire Hathaway Company



T11 4,000 LITRE

Offshore Portable Tank (-40 °C)

General Specification

Dimensions	mm	ft-in	Frame		Steam Heating	None
Length	1,995	6' 6"	Forklift Pockets	Loaded lift fork pockets – 250mm x 100mm, 1000mm centres.	Approvals	T11 UN Portable tank (covering IMDG, ADR/ RID, CFR)
Width	1,995	6' 6"	Lifting Lugs	Fitted with Flemish Splice, Steel ferrule Lifting Sling and Shackles to DNV2.7-1 (2017).		DNVGL-ST-E271 (2017), BS EN ISO 10855 (2018).
Height	2,571	8' 5"				
Capacity	Litres	Gallons	US Gallons			
	4,000	880	1,056			
Shell Material	EN 1.4401/04 (316/316L) Stainless Steel max carbon content 0.3%			Fittings		
Pressures	Working = 4.0 Bar (58.0 psi) Test = 6.0 Bar (87.0 psi) Vacuum = 0.4 Bar (5.8 psi)			Manlid	Fort Vale 500mm, hinged with 8 point fastenings.	
Design Temp	-40°C to +85°C			Airlines	1" BSP top mounted ball valve leading to secondary 1" ball valve operable from ground level and c/w 1" BSP end connector and retained dustcap.	
Design Code	ASME VIII Division 1 where applicable			Bottom Outlet	Fort Vale 3" bottom outlet pad c/w 3" 90 degree highlift footvalve reduced down to 2" pipe extending to a flanged 2" ball valve c/w a 2" BSP male end connector with retained dustcap. Bottom outlet c/w ¾" Sample point, ¾" ball valve, ¾" BSP male end connector and retained dustcap.	
Weights	kgs			Safety Relief Valve	2 ½" BSP Super Maxi pressure / vacuum valve set at 4.4 bar/ 0.21 bar (63.8 /3 psi) with flame gauze fitted.	
Tare	1,610	nominal		Level Gauge	Bayham level gauge fitted to tank body adjacent to bottom outlet.	
Max. Payload	6,390	nominal		Dipstick	Full length dipstick (Litres).	
Max. Gross	8,000					

Note: The above information is an average representation of technical data. Please consult your OCS representative for more specific data.



Visit our website www.exsif-ocs.com

EXSIF OCS Limited, Aberdeen / Gt. Yarmouth: + 44 (0) 1224 976000 Contact: info@exsif-ocs.com